





ACAPULCO 2 S1

ARTICLE 806-6680 **SIZE RANGE** UK 5 - 11

CONTR. TECH. Direct Injected

FEATURES

















DESCRIPTION

The Equator Line is a range offering "good" styling and features. The double density sole features Bata Industrials unique energy returning Tunnelsystem®. A wide footbed and antislip tyre tread sole design reduce the risk of ankle roll and increase slip resistance.

SECTORS	

DESCRIPTION

Construction

Safety Toecap Midsole

Anti-Penetration Sole

Color

Upper

Lining

Insole

Outsole

Fitting

Standard





MAINTENANCE

To keep footwear in usable conditions it is recommended to maintain it always clean and polished. If wet, shoes should be dried at room temperature. Never heat at stove.

WARRANTY

Bata Industrials guarantees quality and durability of their products against any manufacturing defects. It is recommended to use a product suitable for your production activity or service. Quality+ applies to all Bata Industrials Footwear.

DETAIL

Direct Injected

Barton Leather

PU - Grey

PU - Black

1 Width W

S1 A/E/SRC

Bata Xtreme ®-Black

(Non) Woven Fabric

Steel - Impact Resistance 200J

CE EN ISO 20345:2004/A1:2007

Black







GRENADA S1P

ARTICLE 806-6668 **SIZE RANGE** UK 5 - 11

CONTR. TECH. Direct Injected

FEATURES



















DESCRIPTION

The Equator Line is a range offering "good" styling and features. The double density sole features Bata Industrials unique energy returning Tunnelsystem®. A wide footbed and antislip tyre tread sole design reduce the risk of ankle roll and increase slip resistance.

SE	CI	O	RS

DESCRIPTION

Construction

Safety Toecap

Anti-Penetration Sole

Color

Upper

Lining

Insole

Midsole

Outsole

Fitting

Standard







MAINTENANCE

To keep footwear in usable conditions it is recommended to maintain it always clean and polished. If wet, shoes should be dried at room temperature. Never heat at stove.

WARRANTY

Bata Industrials guarantees quality and durability of their products against any manufacturing defects. It is recommended to use a product suitable for your production activity or service. Quality+ applies to all Bata Industrials Footwear.

DETAIL

Direct Injected

Barton Leather

PU - Grey

PU - Black

1 Width W

S1P A/E/P/SRA

Bata Xtreme ®-Black

(Non) Woven Fabric

Steel-Pen.Resistance 1100N

Steel - Impact Resistance 200J

CE EN ISO 20345:2004/A1:2007

Black







DARWIN S1

ARTICLE 806-6662 **SIZE RANGE** UK 5 - 11

CONTR. TECH. Direct Injected

FEATURES

















DESCRIPTION

The Equator Line is a range offering "good" styling and features. The double density sole features Bata Industrials unique energy returning Tunnelsystem®. A wide footbed and antislip tyre tread sole design reduce the risk of ankle roll and increase slip resistance.

_			
SI	EC	ГО	RS

DESCRIPTION

Construction

Safety Toecap Midsole

Anti-Penetration Sole

Color

Upper

Lining

Insole

Outsole

Fitting

Standard







MAINTENANCE

To keep footwear in usable conditions it is recommended to maintain it always clean and polished. If wet, shoes should be dried at room temperature. Never heat at stove.

WARRANTY

Bata Industrials guarantees quality and durability of their products against any manufacturing defects. It is recommended to use a product suitable for your production activity or service. Quality+ applies to all Bata Industrials Footwear.

DETAIL

Direct Injected

Barton Leather

PU - Grey

PU - Black

1 Width W

S1 A/E/SRC

Bata Xtreme ®-Black

(Non) Woven Fabric

Steel - Impact Resistance 200J

CE EN ISO 20345:2004/A1:2007

Black







BARBADOS S1P

ARTICLE 806-6666 **SIZE RANGE** UK 5 - 11

CONTR. TECH. Direct Injected

FEATURES



















DESCRIPTION

The Equator Line is a range offering "good" styling and features. The double density sole features Bata Industrials unique energy returning Tunnelsystem®. A wide footbed and antislip tyre tread sole design reduce the risk of ankle roll and increase slip resistance.

Lining	Bata Xtreme ®-Black
Anti-Penetration Sole	Steel-Pen.Resistance 1100N
Insole	(Non) Woven Fabric
Safety Toecap	Steel - Impact Resistance 200J
Midsole	PU - Grey
Outsole	PU - Black
Fitting	1 Width W
Standard	CE EN ISO 20345:2004/A1:2007
	S1P A/E/P/SRA

DETAIL

Direct Injected

Barton Leather

Black

SECTORS

DESCRIPTION

Construction

Color

Upper







MAINTENANCE

To keep footwear in usable conditions it is recommended to maintain it always clean and polished. If wet, shoes should be dried at room temperature. Never heat at stove.

WARRANTY







CLARK S1P

ARTICLE 806-4681 **SIZE RANGE** UK 5 - 11

CONTR. TECH. Direct Injected

FEATURES

















DESCRIPTION

The Equator Line is a range offering "good" styling and features. The double density sole features Bata Industrials unique energy returning Tunnelsystem®. A wide footbed and antislip tyre tread sole design reduce the risk of ankle roll and increase slip resistance.

SECT	ORS



DESCRIPTION

Construction

Safety Toecap

Anti-Penetration Sole

Color

Upper

Lining

Insole

Midsole

Outsole

Fitting

Standard



MAINTENANCE

To keep footwear in usable conditions it is recommended to maintain it always clean and polished. If wet, shoes should be dried at room temperature. Never heat at stove.

WARRANTY

Bata Industrials guarantees quality and durability of their products against any manufacturing defects. It is recommended to use a product suitable for your production activity or service. Quality+ applies to all Bata Industrials Footwear.

DETAIL

Direct Injected

Barton Leather

PU - Grey

PU - Black

1 Width W

S1P A/E/P/SRA

Bata Xtreme ®-Black

(Non) Woven Fabric

Steel-Pen.Resistance 1100N

Steel - Impact Resistance 200J

CE EN ISO 20345:2004/A1:2007

Brown







BORA S1P

ARTICLE 806-6247 UK 4 - 11 **SIZE RANGE CONTR. TECH. Pouring PU**

FEATURES

















DESCRIPTION

Tropical is an exclusive safety shoes outdoor line with modern and functional design, providing technologies and protection through light and comfortable shoes.

DESCRIPTION	DETAIL
Color	Black
Construction	Pouring PU
Upper	Cow Split Leather (Barton Print)
Lining	Cambrelle - Black
Anti-Penetration Sole	Steel-Pen. Resistance 1100N
Insole	EVA-textile
Safety Toecap	Steel - Impact Resistance 200J
Midsole	PU - Black
Outsole	PU - Black
Fitting	1 Width W
Standard	CE EN ISO 20345:2011
	S1P E/SRA

SECTORS









MAINTENANCE

To keep footwear in usable conditions it is recommended to maintain it always clean and polished. If wet, shoes should be dried at room temperature. Never heat at stove.

WARRANTY







SIROCCO S1P

ARTICLE 806-6248 UK 4 - 11 **SIZE RANGE CONTR. TECH. Pouring PU**

FEATURES

















DESCRIPTION

Tropical is an exclusive safety shoes outdoor line with modern and functional design, providing technologies and protection through light and comfortable shoes.

Lining	Cambrelle - Black
Anti-Penetration Sole	Steel-Pen. Resistance 1100N
Insole	EVA-textile
Safety Toecap	Steel - Impact Resistance 200J
Midsole	PU - Black
Outsole	PU - Black
Fitting	1 Width W
Standard	CE EN ISO 20345:2011
	S1P E/SRA

DETAIL

Pouring PU

Cow Split Leather (Barton Print)

Black

SECTORS

DESCRIPTION

Construction

Color

Upper









MAINTENANCE

To keep footwear in usable conditions it is recommended to maintain it always clean and polished. If wet, shoes should be dried at room temperature. Never heat at stove.

WARRANTY







CONCORD METAL INSOLE 12CM SBP

ARTICLE 806-6249 **SIZE RANGE** UK 5 - 11 **CONTR. TECH.** Cemented

FEATURES

















DESCRIPTION

The Basic Line safety shoe is made of high quality printed Leather with excellent characteristics, and with a high resistant and durable rubber sole.

DESCRIPTION	DETAIL
Color	Black
Construction	Cemented
Upper	Barton Leather
Lining	-
Anti-Penetration Sole	Steel-Pen. Resistance 1100N
Insole	Textile
Safety Toecap	Steel - Impact Resistance 200J
Midsole	-
Outsole	Rubber - Black
Fitting	1 Width W
Standard	NCh. 772/1
	SBP

SECTORS







MAINTENANCE

To keep footwear in usable conditions it is recommended to maintain it always clean and polished. If wet, shoes should be dried at room temperature. Never heat at stove.

WARRANTY







DETAIL

Blue-Grey

Cemented

Suede-Mesh Mesh - Black

Non Woven Fabric

EVA-Mid Grey

Rubber - Black

1 Width W

S1 A/E/SRA

Steel - Impact Resistance 200J

CE EN ISO 20345:2004/A 1: 2007

DALTON S1

ARTICLE 806-2250 **SIZE RANGE** UK 5 - 11 **CONTR. TECH.** Cemented

FEATURES



















DESCRIPTION

SportMates feature the reassuring strength of steel toe caps and durable heat, oil and acid resistant rubber outsoles, are light and flexible to wear and have optimum climate control inside the shoe for day long comfort.

_			n	
١,	ю.	16	H	•

DESCRIPTION

Construction

Safety Toecap Midsole

Anti-Penetration Sole

Color

Upper

Lining

Insole

Outsole

Fitting

Standard







MAINTENANCE

To keep footwear in usable conditions it is recommended to maintain it always clean and polished. If wet, shoes should be dried at room temperature. Never heat at stove.

WARRANTY







MENDEL S1

ARTICLE 806-6251 UK 5 - 11 **SIZE RANGE CONTR. TECH.** Cemented

FEATURES















DESCRIPTION

SportMates feature the reassuring strength of steel toe caps and durable heat, oil and acid resistant rubber outsoles, are light and flexible to wear and have optimum climate control inside the shoe for day long comfort.

DESCRIPTION	DETAIL
Color	Black-Grey
Construction	Cemented
Upper	Suede-Mesh
Lining	Mesh - Black
Anti-Penetration Sole	-
Insole	Non Woven Fabric
Safety Toecap	Steel - Impact Resistance 200J
Midsole	EVA-Mid Grey
Outsole	Rubber - Black
Fitting	1 Width W
Standard	CE EN ISO 20345:2004/A 1: 2007
	S1 A/E/SRA

SECTORS







MAINTENANCE

To keep footwear in usable conditions it is recommended to maintain it always clean and polished. If wet, shoes should be dried at room temperature. Never heat at stove.

WARRANTY







BICKZ 205 S1P

ARTICLE 806-8252
SIZE RANGE UK 5 - 11
CONTR. TECH. Cemented

FEATURES



DESCRIPTION

Bickz is a technology based product that uses the latest in composite materials to provide outstanding protection for your feet. Bickz performs comfortably in industrial and professional environments.

	DETAIL
Color	Grey-Orange
Construction	Cemented
Upper	Nubuck
Lining	Bickz Cool System - Black
Anti-Penetration Sole	Flexguard-Pen.Resistance 1100N
Insole	Flexguard-Pen.Resistance 1100N
Safety Toecap	Composite-Impact.Resistance 200J
Midsole	Rubber - Black
Outsole	1 Width W
Fitting	CE EN ISO 20345:2004/A 1: 2007
Standard	S1 A/E/P/SRA/HRO

SECTORS







MAINTENANCE

To keep footwear in usable conditions it is recommended to maintain it always clean and polished. If wet, shoes should be dried at room temperature. Never heat at stove.

WARRANTY







BICKZ 206 S1P

ARTICLE 806-6253
SIZE RANGE UK 5 - 11
CONTR. TECH. Cemented

FEATURES



DESCRIPTION

Bickz is a technology based product that uses the latest in composite materials to provide outstanding protection for your feet. Bickz performs comfortably in industrial and professional environments.

- P P	
Lining	Bickz Cool System - Black
Anti-Penetration Sole	Flexguard-Pen.Resistance 1100N
Insole	Flexguard-Pen.Resistance 1100N
Safety Toecap	Composite-Impact.Resistance 200J
Midsole	Rubber - Black
Outsole	1 Width W
Fitting	CE EN ISO 20345:2004/A 1: 2007
Standard	S1 A/E/P/SRA/HRO

DETAIL

Black-Grey

Cemented

Nubuck

SECTORS

DESCRIPTION

Construction

Color

Upper







MAINTENANCE

To keep footwear in usable conditions it is recommended to maintain it always clean and polished. If wet, shoes should be dried at room temperature. Never heat at stove.

WARRANTY







BICKZ PERFORMANCE 2-2 BROWN MESH LINING SBP

ARTICLE 806-4254

SIZE RANGE UK 5 - 11

CONTR. TECH. Cemented

FEATURES



DESCRIPTION

Bickz is a technology based product that uses the latest in composite materials to provide outstanding protection for your feet. Light in weight and fully flexible, Bickz performs comfortably in industrial and professional environments.

DESCRIPTION	DETAIL
Color	Brown
Construction	Cemented
Upper	Pull Up Leather
Lining	Mesh
Anti-Penetration Sole	Composite-Pen.Resistance 1100N
Insole	Anti Penetration
Safety Toecap	Composite-Impact.Resistance 200J
Midsole	Phylon-Grey
Outsole	Rubber - Black
Fitting	1 Width W
Standard	NCh. 772/1
	ASTM F2413-05
	SBP

SECTORS











MAINTENANCE

To keep footwear in usable conditions it is recommended to maintain it always clean and polished. If wet, shoes should be dried at room temperature. Never heat at stove.

WARRANTY







BICKZ PERFORMANCE 3-1 WOMEN LINE MESH LINING SBP

ARTICLE 506-6316

SIZE RANGE UK 4 - 8

CONTR. TECH. Cemented

FEATURES



DESCRIPTION

Bickz is a technology based product that uses the latest in composite materials to provide outstanding protection for your feet. Light in weight and fully flexible, Bickz performs comfortably in industrial and professional environments.

DESCRIPTION	DETAIL
Color	Black
Construction	Cemented
Upper	Waterproof Leather
Lining	Mesh
Anti-Penetration Sole	Composite-Pen.Resistance 1100N
Insole	Anti Penetration
Safety Toecap	Composite-Impact.Resistance 200J
Midsole	Phylon-Grey
Outsole	Rubber - Black
Fitting	1 Width W
Standard	NCh. 772/1
	ASTM F2413-05
	SBP

SECTORS











MAINTENANCE

To keep footwear in usable conditions it is recommended to maintain it always clean and polished. If wet, shoes should be dried at room temperature. Never heat at stove.

WARRANTY







DETAIL

Pouring PU

EVA-textile

PU - Black PU - Black

1 Width W

ESD III EN 61340-4-3

Cambrelle - Black

Cow Split Leather (Smooth Print)

Steel - Impact Resistance 200J

Black

BEAT ESD

ARTICLE 806-6251 **SIZE RANGE** UK 4 -11 CONTR. TECH. Pouring PU

FEATURES















DESCRIPTION

ESD (ElectroStatic Dissipative) shoes have an electrical resistance between 0.1 and 100 (MΩ), measured according to BS EN 61340-4-3: 2002 (IEC 61340-4-3:2001). ESD shoes are thus guaranteed to have an extremely low electrical resistance under any conditions in order to prevent a strong, uncontrolled electrostatic charge.

SECTORS

DESCRIPTION

Anti-Penetration Sole

Construction

Safety Toecap

Color

Upper

Lining

Insole

Midsole

Outsole Fitting

Standard









MAINTENANCE

To keep footwear in usable conditions it is recommended to maintain it always clean and polished. If wet, shoes should be dried at room temperature. Never heat at stove.

WARRANTY