



SWIFT ESD 3

ARTICLE 808-1012 **SIZE RANGE** UK 3 -11 CONTR. TECH. Cemented

FEATURES

















DESCRIPTION

ESD (ElectroStatic Dissipative) shoes have an electrical resistance between 0.1 and 100 (MΩ), measured according to BS EN 61340-4-3: 2002 (IEC 61340-4-3:2001). ESD shoes are thus guaranteed to have an extremely low electrical resistance under any conditions in order to prevent a strong, uncontrolled electrostatic charge.

SECTORS

DESCRIPTION

Anti-Penetration Sole

Construction

Safety Toecap

Color

Upper

Lining

Insole

Midsole

Outsole

Standard

Fitting









DETAIL

Cemented

Action Leather

Bata Xtreme

EVA-textile

Rubber

Rubber

1 Width W

EN 61340-4-3 ESD

White



-Composite Impact Resistance 200J

MAINTENANCE

To keep footwear in usable conditions it is recommended to maintain it always clean and polished. If wet, shoes should be dried at room temperature. Never heat at stove.

WARRANTY

Bata Industrials guarantees quality and durability of their products against any manufacturing defects. It is recommended to use a product suitable for your production activity or service. Quality+ applies to all Bata Industrials Footwear.