

# TORQUE METERS: KTM-15, KTM-150, KTM-250

## Features:

- Ideal for Electric Screwdrivers
- Easy to use and set-up
- Comes with Certificate of Calibration
- Data Output-1.0 USB Port-Cable not included
- Store up to 800 readings
- Selectable Measuring Units: Lbf.in, Kgf.cm, Nm
- Portable-Rechargeable Battery -Long Life
- Auto Zero feature
- Program Hi and Low Torque Limits
- Display readings/statistics- Minimum, Maximum and Average Torque for group of run downs
- Peak, Real Time and Peak Down measuring modes (selectable)
- Measure both clockwise and counterclockwise
- Includes: AC Charger-Run Down Joints, All in a protective carry case



**KTM-150**

| Specifications                                 |  |  |                                     |
|--|--|--|-------------------------------------|
| Model  | KTM-15                                       | KTM-150                                    | KTM-250                             |
| Measuring Ranges (kgf.cm)<br>(lbf.in)<br>(N.m) | 0.1-15.0<br>0.09-13.02<br>0.01-1.47          | 1.5-150.0<br>1.3-130.02<br>0.15-14.7       | 3.0-250.0<br>2.6-217.0<br>0.29-24.5 |
| Accuracy                                       | Within $\pm 0.5\%$                           |  |                                     |
| Power Supply                                   | 1.2V Battery X5                              |  |                                     |
| Charging Time                                  | Within 8 hours                               |  |                                     |
| Continuous Operation At Full Charge            | 12 Hours                                     |  |                                     |
| Battery  | Rechargeable 300 times or more               |  |                                     |
| Dimension(mm)                                  | 123x230x65(H)                                | 180x130x34(H)                              | 220x160x50(H)                       |
| Weight(kg)(lbs)                                | 2.0kg/4.4lbs                                 | 1.5kg/3.3lbs                               | 2.0kg/4.4lbs                        |
| Special Charger                                | Input AC120V,<br>220-240V Output DC12V 500mA | Input AC120V, 220-240V Output DC7.5V 500mA |                                     |
| Accessory                                      | Test Joints:<br>AJ-3<br>AJ-15                | Test Joints:<br>AJ-15K<br>AJ-50<br>AJ-150  | Test Joints:<br>AJ-300              |