

## OPTIONAL ACCESSORIES

### ILLUMINATORS

#### Model MIC-56

WHITE LED RING ILLUMINATOR  
with non-step brightness adjustment

- \* 54 pcs. LED (light-emitting diode)
- \* Long life time
- \* Low temperature
- \* No change of color temperature
- \* Flicker-free



#### Model LED-60T

WHITE LED RING ILLUMINATOR  
with 7-step brightness adjustment & four kinds  
of lighting modes (1/4, 2/4, 3/4 & full lighting)

- \* 60 pcs. LED (light-emitting diode)
- \* Long life time
- \* Low temperature
- \* No change of color temperature
- \* Flicker-free



#### Model LED40AR

"COLD LIGHT" 40W OPTICAL FIBER ILLUMINATOR  
with Ring Light Guide

- Length 1000mm
- Long life up to 20000H (no guaranteed)



#### Model LED40AD

"COLD LIGHT" 40W OPTICAL FIBER ILLUMINATOR  
with Double Branch Light Guide

- Length 500mm
- Long life up to 20000H (no guaranteed)

\*Single Branch Light Guide type also available (Model LED40AS)



#### Model LED40FL

FOCUSING LENS for LED40AD & LED40AS

- Illumination distance : 20-200mm
- Illumination area : 10-40mm diameter
- External dimensions : 24mm dia. x 69.61mm (max.)



#### Model LTA-1

LED ILLUMINATOR  
with flexible twin arm



### MONITOR HOLDER

#### Model Z1015

MONITOR HOLDER




## SHOP MICROSCOPES




#### Model M1752 Model M1754

For printing,  
machining,  
inspection,  
measurements, etc



M1752  
40x, with scale  
3.0mm/0.1"



M1754  
100x, with scale  
1.0mm/0.05"

Model	M1752	M1754
Magnification (Field of View)	40x (4.5mm)	100x (1.8mm)
Objective Lens	4x	10x
Focusable Eyepiece	10x with scale	10x with scale
Measuring Range	3.0mm/0.1"	1.0mm/0.05"
Minimum Graduation	0.02mm/0.001"	0.01mm/0.001"
Working Distance	15mm	5.5mm
Height	200mm	
Width	65mm	
Net Weight	570g	580g
Accessory	Penlight	
Packing	Carton box	